

WAM™ Wireless Acquisition Module

12-Lead ECG Acquisition Module With Wireless Technology

Specifications

Product Features

- **Convenient Patient Access** — Equivalent in size and weight to a conventional wired patient cable, the WAM™ Wireless Acquisition Module provides freedom of movement for the clinician while acquiring electrocardiograms and performing cardiac stress testing exams.
- **Easy ECG Acquisition at the Electrocardiograph** — ECG acquisition can be initiated at the WAM module or the electrocardiograph. The module offers ON/OFF, 12-lead ECG acquisition and rhythm printing at the bedside with the simple press of a button. Visual and audible feedback is provided at the WAM module.
- **Small Spaces Are No Obstacle** — The need to maneuver the electrocardiograph through the doorway to the patient's bedside is eliminated; this is particularly advantageous in critical situations or when the patient is in isolation.
- **Point-to-Point Connection** — Dedicated and secure communication links the WAM module to a single electrocardiograph or cardiac stress system.
- **Diagnostic-Quality ECG** — Welch Allyn wireless technology features full diagnostic-quality ECG with a high-fidelity acquisition sampling rate of 40,000 samples per second per channel—a benefit for accurate pacemaker detection. Elimination of the cable reduces a source of artifact resulting in high-quality ECG tracings.
- **Efficient Power Management** — Under typical usage, the battery-operated WAM module can acquire 250 resting ECGs. Advanced power management automatically turns it off.



WAM Wireless Acquisition Module

Feature	Specification*
Instrument Type	12-lead wireless acquisition module for resting ECG
Input Channels	12-lead signal acquisition and transmission
ECG Leads Transmitted	I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5 and V6
Module Transmission Protocol	Bidirectional and frequency hopping; beacon and response method links a single acquisition module to a single electrocardiograph or cardiac stress system
Frequency Range	2400.96 MHz to 2482.56 MHz
Module and Receiver Distance	Approximately 10 feet (3 meters)
Lead Set	RA, LA, RL, LL, V1, V2, V3, V4, V5 and V6 (R, L, N, F, C1, C2, C3, C4, C5 and C6) with detachable lead wires
Sampling Rate	40,000 samples/second/channel acquisition; 1,000 samples/second/channel transmitted for analysis
Resolution	1.875 microvolt LSB
User Interface	Three-button operation: ON/OFF, 12-lead ECG acquisition and rhythm strip acquisition
Defibrillator Protection	Complies with AAMI standards and IEC 60601-2-25
Special Functions	LED indication of power status, operating mode, lead fault and remaining battery charge
Device Classification	Type CF, battery operated
Weight	6.7 oz. (190 g) with battery
Dimensions	4.45 x 4.25 x 1.1" (11.3 x 10.8 x 2.79 cm)
Battery	1 AA alkaline battery typically powers WAM module for acquisition of 250 resting ECGs

Specifications subject to change without notice.

For more information, contact your local Welch Allyn representative or visit www.welchallyn.com.



Clinical excellence. Connected solutions. Continuous innovation.
Welch Allyn Cardiology is proud to be powered by Mortara.

Welch Allyn, Inc.
4341 State Street Road
Skaneateles Falls, NY 13153 USA
(p) 800.535.6663 (f) 315.685.3361

© 2018 Welch Allyn MC14823 80022571 Ver A 2018-04

www.welchallyn.com

WelchAllyn®